## Aspen/Rentals, Inc.

23603 N Highway 288. Angleton, TX 77515

(979) 864-3990


## The Next Generation Sludge/Filtrate Pump Has Arrived . . .

## WITH UNPARALLED PERFORMANCE!!

4 Inch Centrifugal Sludge/Filtrate Pump

Complete with:

Breaker 15 HP VFD Inverter Duty Motor Water-tight Control Panel 50 Ft. SO Power Cord Metal Skid w/ Feet (for easy lifting) Cold Water Drain 4" Caps with Chains (during transport)





## **4 Inch Pump Specifications**

| ltom                                   | Sowaga/Trach Contrifugal Dump  |
|--|--|
| Item<br>HP                             | Sewage/Trash Centrifugal Pump 15   |
|  |  |
| Phase                                  | 3  |
| Voltage                                | 230/460  |
| Amps                                   | 34.6/17.3  |
| Hz                                     | 60   |
| Inlet/Outlet (In.)                     | 4  |
| Motor Enclosure                        | TEFC   |
| NEMA/IEC Frame                         | 215JM  |
| Motor RPM                              | 3450   |
| Motor Type                             | 3 - Phase  |
| Service Factor                         | 1.25   |
| Wetted Materials                       | CI, SS, Silicon Carbide, Buna N, BR  |
| Impeller Material                      | Stainless Steel  |
| Housing Material                       | Cast Iron  |
| Volute Material                        | Cast Iron  |
| Shaft Material                         | Steel  |
| Screw Material                         | Zinc Plated  |
| Seal Type                              | Mechanical   |
| Seal Material                          | Carbon/Ceramic/Buna-N  |
| Max. Liquid Temp. (F)                  | 160  |
| GPM of Water @ 40 Ft. of Head          | 485  |
| GPM of Water @ 50 Ft. of Head          | 405  |
| GPM of Water @ 60 Ft. of Head          | 360  |
| GPM of Water @ 70 Ft. of Head          | 300  |
| GPM of Water @ 80 Ft. of Head          | 240  |
| GPM of Water @ 90 Ft. of Head          | 175  |
| Max. Head (Ft.)                        | 120  |
| Best Efficiency GPM @ Head (Ft.)       | 410 @ 49   |
| Best Efficiency Range GPM @ Head (Ft.) |  |
| Max. Specific Gravity                  | 1.0  |
| Max. Case Pressure (PSI)               | 60   |
| Max. Fluid Viscosity                   | 100 SSU  |
| Inlet Pressure (PSI)                   | 10   |
| Impeller Type                          | Semi-open  |
| Bearing Type                           | Ball   |
| Duty                                   | Continuous   |
| Max. Dia. Solids (In.)                 | 1.33   |
| Port Rotation                          | None   |
| Drain Plug                             | 3/4" NPT   |
| Agency Compliance                      | None   |
|  |  |
| Application                            | Process, Liquid Transfer, Irrigation, Clear or Gray Water and Sewage Treatment |
| For Use With                           | Water and Nonflammable Liquids Compatible with Pump Component Materials        |
| Height (In.)                           | 12.97  |
|  | 30.52  |
| Length (In.)<br>Width (In.)            |  |
| Width (In.)<br>Includes                | 14.10<br>Strainer and Manual   |
| includes                               | Strainer and Manual  |